

**REMARKS****Status of the Claims**

Applicant has amended claims 1 and 5 and cancelled claims 14, and 17-30. Claims 1-13 remain under consideration.

Claim 1 is amended above to contain the limitations of cancelled claim 29 and Claim 5 is amended above to contain the limitations of cancelled claim 30. There were no intervening claims in either claim. Therefore, claims 1 and 5 now contain patentable subject matter, as defined by the Examiner in the statement of Allowable Subject Matter. Since dependent claims Claims 2-4, 6-8, and 10-13 are dependent on allowable claims 1 and 5, such dependent claims also define patentable subject matter.

The claims of this application are amended after final rejection to place this application in condition for allowance. If there are any questions in this regard the Examiner is requested to call Applicant's Attorney, Ralph Gelling, at 203-259-1800, ext 136.

**SUMMARY**

In view of the amendments to this application, favorable action by the Examiner is respectfully requested.

Please charge Deposit Account No. 16-1350 for any fee deficiencies with regard to the filing of this Amendment.

Respectfully submitted,



Ralph D. Gelling, Reg No. 24,689  
Perman & Green, LLP  
425 Post Road  
Fairfield, CT 06824  
203-259-1800  
Customer No. 2512

3/19/03  
Date

CERTIFICATE OF FACSIMILE TRANSMISSION

I hereby certify that this correspondence is being transmitted by facsimile to 703/872-9314 the date indicated below, addressed to the Box AF, Commissioner of Patents, Washington, D.C. 20231.

Date: 3/19/03

Signature: Carolina Rodriguez  
Person Making Deposit

**APPENDIX A to Response to Office Action Mailed: 12/20/02**  
**(Amendments with changes highlighted)**  
**Application Ser. No. 09/019,614, Art Unit: 2644**

For the Examiner's convenience all of the claims whether or not amended are stated below:

1. (Amended Four Times) A method for setting audio parameters controlling processing in a digital signal processor (4) in an electronic device (1) comprising at least one auxiliary device connection (10) for connecting at least one auxiliary device (11), wherein at least some of the audio parameters are loaded into the digital signal processor (4) during operation of the electronic device (1) from the auxiliary device (11), said auxiliary device (11) conducting two way communication of digital data with said electronic device (1), further comprising operating a microcontroller in said auxiliary device to conduct said two way communication.

2. The method according to claim 1, wherein the audio parameters are loaded from the auxiliary device (11) via the auxiliary device connection (10).

3. The method according to claim 1, wherein the audio parameters are loaded at the stage when the auxiliary device (11) is connected to or detached from the electronic device (1) or when the auxiliary device changes its audio mode.

4. The method according to claim 3, wherein the electronic device (1) comprises further a detection line (23) and a connection bus (12), and that the connection of the auxiliary device (11) is detected on the basis of a change in the voltage of the detection line (23) or on the basis of messages transferred via the connection bus (12) between the electronic device (1) and the auxiliary device (11).

5. (Amended Three Times) An electronic device (1) comprising:

a digital signal processor (4) for processing audio signals;

means (22) for storing audio parameters controlling the processing of audio signals in the digital signal processor (4), and

an auxiliary device connection (10) for connecting an auxiliary device (11) with the electronic device (1),

wherein the electronic device (1) further comprises communication means for loading the audio parameters into the means (22) for storing the audio parameters from the auxiliary device (11), and for conducting two way communication of digital data with the auxiliary device (11), wherein said communication means communicates with a microcontroller in said auxiliary device.

6. The device according to claim 5, further comprising a detection line (23) and a connection bus (12) and means (2, 24) for detecting the connection of the auxiliary device (11) into the auxiliary device connection (10) either on the basis of a change in the voltage of the detection line (23) or on the basis of the messages transferred via a detection bus (12) between the electronic device (1) and the auxiliary device (11).

7. The device according to claim 5, further comprising a transmitter/receiver unit (6) of a mobile station.

8. The device (1) according to claim 5, wherein the device is a

mobile station.

9. The device according to claim 8, wherein the auxiliary device (11) comprises an auxiliary loudspeaker (26) and an auxiliary microphone (27).

10. The method according to claim 1, wherein said audio parameters are other than data used to recognize the type of auxiliary device.

11. The method according to claim 1, wherein all of said audio parameters are loaded into the digital signal processor from the auxiliary device.

12. The device according to claim 5, wherein said audio parameters are other than data used to recognize the type of auxiliary device.

13. The device according to claim 5, wherein all of said audio parameters are loaded into the digital signal processor from the auxiliary device.

14. (Cancelled)

17. - 30. (Cancelled)